



LAC-12

EXPLORE THE MODEL OPTIONS
AVAILABLE FOR OUR 12-LITER
THERMOSTATIC BATH



LAC-12-CD:

- Precise temperature control / For internal and external applications
- Bright white displays, clearly visible from a distance
- Exceptionally quiet operation
- LED temperature indication
- Simple operation / USB connection
- Class III (FL) compliant with DIN 12876-1
- Electrostatic-coated housing

ESPECIFICAÇÕES TÉCNICAS

- Working temperature range: Ambient +5°C to +200°C
- Temperature constancy: $\pm 0.03^{\circ}\text{C}$
- Adjustment/indication resolution: 0.01°C
- Heating power: 2 kW
- Pump flow rate: 16 L/min
- Pump pressure: 0.33 bar
- Usable area (opening): 145 x 210 mm
- Depth: 200 mm
- Volume: 12.5 L
- External dimensions: 29.6 x 43.6 x 49.3 cm (WxDxH)
- Total power: 2000 W
- Voltage: 230Vac 50/60Hz

LAC-12-DD:

- Precise temperature control / For internal and external applications
- Bright white displays, clearly visible from a distance
- Exceptionally quiet operation
- LED temperature indication
- Simple operation / USB connection
- Class III (FL) compliant with DIN 12876-1
- Electrostatic-coated housing

ESPECIFICAÇÕES TÉCNICAS

- Working temperature range: Ambient +5°C to +200°C
- Temperature constancy: $\pm 0.01^{\circ}\text{C}$
- Adjustment/indication resolution: 0.01°C
- Heating power: 2 kW
- Pump flow rate: 8–27 L/min
- Pump pressure: 0.1–0.7 bar
- Usable area (opening): 145 x 210 mm
- Depth: 200 mm
- Volume: 12.5 L
- External dimensions: 29.6 x 43.6 x 49.3 cm (WxDxH)
- Total power: 2000 W
- Voltage: 230Vac 50/60Hz

LAC-F12-CD:

- Precise temperature control / For external applications
- Bright white displays, clearly visible from a distance
- Exceptionally quiet operation
- LED temperature indication
- Simple operation / USB connection
- Class III (FL) compliant with DIN 12876-1
- Electrostatic-coated housing

TECHNICAL SPECIFICATIONS

- Working temperature range: -28°C to +150°C
- Temperature constancy: $\pm 0.03^{\circ}\text{C}$
- Adjustment/indication resolution: 0.01°C
- Heating power: 2 kW
- Pump flow rate: 16 L/min
- Pump pressure: 0.33 bar
- Usable area (opening): 145 x 210 mm
- Depth: 200 mm
- Volume: 12.5 L
- External dimensions: 33.6 x 47.8 x 72.65 cm (WxDxH)
- Total power: 2300 W
- Voltage: 230Vac 50/60Hz

LAC-F12-DD:

- Precise temperature control / For external applications
- Bright white displays, clearly visible from a distance
- Exceptionally quiet operation
- LED temperature indication
- Simple operation / USB connection
- Class III (FL) compliant with DIN 12876-1
- Electrostatic-coated housing

TECHNICAL SPECIFICATIONS

- Working temperature range: -28°C to +150°C
- Temperature constancy: $\pm 0.01^{\circ}\text{C}$
- Adjustment/indication resolution: 0.01°C
- Heating power: 2 kW
- Pump flow rate: 8–27 L/min
- Pump pressure: 0.1–0.7 bar
- Usable area (opening): 145 x 210 mm
- Depth: 200 mm
- Volume: 12.5 L
- External dimensions: 33.6 x 47.8 x 72.65 cm (WxDxH)
- Total power: 2300 W
- Voltage: 230Vac 50/60Hz

Our baths feature Julabo controllers, offering high precision and temperature stability solutions.