



LAC-21

EXPLORE THE MODEL OPTIONS
AVAILABLE FOR OUR 21-LITER
THERMOSTATIC BATH



LAC-21-CD:

- Precise temperature control / For internal and external applications
- Bright white displays, easily visible from a distance
- Exceptionally quiet operation
- LED temperature display
- Easy to operate / USB connection
- Class III (FL) according to DIN 12876-1
- Cabinet with electrostatic paint finish

TECHNICAL SPECIFICATIONS

- Operating temperature range: ambient +5°C to +200°C
- Temperature stability (°C): ± 0.03
- Adjustment/indication resolution: 0.01°C
- Heating power (kW): 2
- Pump flow rate (l/min): 16
- Pump pressure (bar): 0.33
- Usable area (opening): 30 x 35,5 (mm)
- Depth: 150 (mm)
- Volume: 21L
- External dimensions: 33 x 60,5 x 44,5 cm (LxWxH)
- Total power: 2000 W
- Voltage: 230Vac 50/60Hz

LAC-21-DD:

- Precise temperature control / For internal and external applications
- Bright white displays, easily visible from a distance
- Exceptionally quiet operation
- LED temperature display
- Easy to operate / USB connection
- Class III (FL) according to DIN 12876-1
- Cabinet with electrostatic paint finish

TECHNICAL SPECIFICATIONS

- Temperature Range: Ambient +5°C to +200°C
- Temperature Stability: $\pm 0.01^\circ\text{C}$
- Resolution: 0.01°C (for adjustment and indication)
- Heating Power: 2 kW
- Pump Flow Rate: 8 - 27 L/min
- Pump Pressure: 0.1 to 0.7 bar
- Usable Area (opening): 30 x 35.5 mm
- Depth: 150 mm
- Volume: 21 L
- External Dimensions: 33 x 60.5 x 44.5 cm (LxWxH)
- Total Power: 2000 W
- Voltage: 230 Vac, 50/60Hz

LAC-F21-CD:

- Precise temperature control / For internal and external applications
- Bright white displays, easily visible from a distance
- Exceptionally quiet operation
- LED temperature display
- Easy to operate / USB connection
- Class III (FL) according to DIN 12876-1

TECHNICAL SPECIFICATIONS

- Temperature Range: -20°C to +150°C
- Temperature Stability: $\pm 0.03^\circ\text{C}$
- Resolution: 0.01°C (for adjustment and indication)
- Heating Power: 2 kW
- Pump Flow Rate: 16 L/min
- Pump Pressure: 0.33 bar
- Usable Area (opening): 34 x 28 mm
- Depth: 150 mm
- Volume: 21 L
- External Dimensions: 39.7 x 67.3 x 72.8 cm (LxWxH)
- Total Power: 2300 W
- Voltage: 230 Vac, 50/60Hz

LAC-F21-DD:

- Precise temperature control / For internal and external applications
- Bright white displays, easily visible from a distance
- Exceptionally quiet operation
- LED temperature display
- Easy to operate / USB connection
- Class III (FL) according to DIN 12876-1

TECHNICAL SPECIFICATIONS

- Temperature Range: -20°C to +150°C
- Temperature Stability: $\pm 0.01^\circ\text{C}$
- Resolution: 0.01°C (for adjustment and indication)
- Heating Power: 2 kW
- Pump Flow Rate: 8 - 27 L/min
- Pump Pressure: 0.1 to 0.7 bar
- Usable Area (opening): 34 x 28 mm
- Depth: 150 mm
- Volume: 21 L
- External Dimensions: 39.7 x 67.3 x 72.8 cm (LxWxH)
- Total Power: 2300 W
- Voltage: 230 Vac, 50/60Hz

Our baths feature Julabo controllers, offering high precision and temperature stability solutions.