



LAC-28

EXPLORE THE MODEL OPTIONS
AVAILABLE FOR OUR 28-LITER
THERMOSTATIC BATH



LAC-28-CD:

- Precise temperature control / For internal and external applications
- Bright white displays, clearly visible from a distance
- Exceptionally quiet operation
- LED temperature indication
- Simple operation / USB connection
- Class III (FL) compliant with DIN 12876-1
- Electrostatic-coated housing

TECHNICAL SPECIFICATIONS

- Working temperature range: Ambient +5°C to +150°C
- Temperature constancy: $\pm 0.03^\circ\text{C}$
- Adjustment/indication resolution: 0.01°C
- Heating power: 2 kW
- Pump flow rate: 16 L/min
- Pump pressure: 0.33 bar
- Usable area (opening): 180 x 530 mm
- Depth: 300 mm
- Volume: 28.6 L
- External dimensions: 36.5 x 64.85 x 50 cm (WxDxH)
- Total power: 2000 W
- Voltage: 230Vac 50/60Hz

LAC-28-DD:

- Precise temperature control / For internal and external applications
- Bright white displays, clearly visible from a distance
- Exceptionally quiet operation
- LED temperature indication
- Simple operation / USB connection
- Class III (FL) compliant with DIN 12876-1
- Electrostatic-coated housing

TECHNICAL SPECIFICATIONS

- Working temperature range: Ambient +5°C to +150°C
- Temperature constancy: $\pm 0.01^\circ\text{C}$
- Adjustment/indication resolution: 0.01°C
- Heating power: 2 kW
- Pump flow rate: 8–27 L/min
- Pump pressure: 0.1–0.7 bar
- Usable area (opening): 180 x 530 mm
- Depth: 300 mm
- Volume: 28.6 L
- External dimensions: 36.5 x 64.85 x 50 cm (WxDxH)
- Total power: 2000 W
- Voltage: 230Vac 50/60Hz

LAC-F28-CD:

- Precise temperature control / For external applications
- Bright white displays, clearly visible from a distance
- Exceptionally quiet operation
- LED temperature indication
- Simple operation / USB connection
- Class III (FL) compliant with DIN 12876-1
- Electrostatic-coated housing

TECHNICAL SPECIFICATIONS

- Working temperature range: -28°C to $+150^\circ\text{C}$
- Temperature constancy: $\pm 0.03^\circ\text{C}$
- Adjustment/indication resolution: 0.01°C
- Heating power: 2 kW
- Pump flow rate: 16 L/min
- Pump pressure: 0.33 bar
- Usable area (opening): 180 x 530 mm
- Depth: 300 mm
- Volume: 28.6 L
- External dimensions: 68.6 x 51.2 x 80.5 cm (WxDxH)
- Total power: 2300 W
- Voltage: 230Vac 50/60Hz

LAC-F28-DD:

- Precise temperature control / For external applications
- Bright white displays, clearly visible from a distance
- Exceptionally quiet operation
- LED temperature indication
- Simple operation / USB connection
- Class III (FL) compliant with DIN 12876-1
- Electrostatic-coated housing

TECHNICAL SPECIFICATIONS

- Working temperature range: Ambient -28°C to $+150^\circ\text{C}$
- Temperature constancy: $\pm 0.01^\circ\text{C}$
- Adjustment/indication resolution: 0.01°C
- Heating power: 2 kW
- Pump flow rate: 8–27 L/min
- Pump pressure: 0.1–0.7 bar
- Usable area (opening): 180 x 530 mm
- Depth: 300 mm
- Volume: 28.6 L
- External dimensions: 68.6 x 51.2 x 80.5 cm (WxDxH)
- Total power: 2300 W
- Voltage: 230Vac 50/60Hz

Our baths feature Julabo controllers, offering high precision and temperature stability solutions.