

**LAC-60**

EXPLORE THE MODEL OPTIONS  
AVAILABLE FOR OUR 120-LITER  
THERMOSTATIC BATH



## LAC-60-CD:

- Precise temperature control / For internal and external applications
- Bright white displays, clearly visible from a distance
- Exceptionally quiet operation
- LED temperature indication
- Simple operation / USB connection
- Class III (FL) compliant with DIN 12876-1
- Electrostatic-coated housing

### TECHNICAL SPECIFICATIONS

- Working temperature range: Ambient +5°C to +200°C
- Temperature constancy:  $\pm 0.03^\circ\text{C}$
- Adjustment/indication resolution:  $0.01^\circ\text{C}$
- Heating power: 4 kW
- Pump flow rate: 16 L/min
- Pump pressure: 0.33 bar
- Usable area (opening): 410 x 778 mm
- Depth: 397 mm
- Volume: 125 L
- External dimensions: 47.8 x 103 x 83.5 cm (WxDxH)
- Total power: 4000 W
- Voltage: 230Vac 50/60Hz

## LAC-60-DD:

- Precise temperature control / For internal and external applications
- Bright white displays, clearly visible from a distance
- Exceptionally quiet operation
- LED temperature indication
- Simple operation / USB connection
- Class III (FL) compliant with DIN 12876-1
- Electrostatic-coated housing

### TECHNICAL SPECIFICATIONS

- Working temperature range: Ambient +5°C to +200°C
- Temperature constancy:  $\pm 0.01^\circ\text{C}$
- Adjustment/indication resolution:  $0.01^\circ\text{C}$
- Heating power: 4 kW
- Pump flow rate: 8–27 L/min
- Pump pressure: 0.1–0.7 bar
- Usable area (opening): 410 x 778 mm
- Depth: 397 mm
- Volume: 125 L
- External dimensions: 47.8 x 103 x 83.5 cm (WxDxH)
- Total power: 4000 W
- Voltage: 230Vac 50/60Hz

## LAC-F60-CD:

- Precise temperature control / For external applications
- Bright white displays, clearly visible from a distance
- Exceptionally quiet operation
- LED temperature indication
- Simple operation / USB connection
- Class III (FL) compliant with DIN 12876-1
- Electrostatic-coated housing

### TECHNICAL SPECIFICATIONS

- Working temperature range:  $0^\circ\text{C}$  to +200°C
- Temperature constancy:  $\pm 0.03^\circ\text{C}$
- Adjustment/indication resolution:  $0.01^\circ\text{C}$
- Heating power: 4 kW
- Pump flow rate: 16 L/min
- Pump pressure: 0.33 bar
- Usable area (opening): 593 x 485 mm
- Depth: 428 mm
- Volume: 120 L
- External dimensions: 61.8 x 89 x 126.3 cm (WxDxH)
- Total power: 4000 W
- Voltage: 230Vac 50/60Hz

## LAC-F60-DD:

- Precise temperature control / For external applications
- Bright white displays, clearly visible from a distance
- Exceptionally quiet operation
- LED temperature indication
- Simple operation / USB connection
- Class III (FL) compliant with DIN 12876-1
- Electrostatic-coated housing

### TECHNICAL SPECIFICATIONS

- Working temperature range:  $0^\circ\text{C}$  to +200°C
- Temperature constancy:  $\pm 0.01^\circ\text{C}$
- Adjustment/indication resolution:  $0.01^\circ\text{C}$
- Heating power: 4 kW
- Pump flow rate: 8–27 L/min
- Pump pressure: 0.1–0.7 bar
- Usable area (opening): 593 x 485 mm
- Depth: 428 mm
- Volume: 120 L
- External dimensions: 61.8 x 89 x 126.3 cm (WxDxH)
- Total power: 4000 W
- Voltage: 230Vac 50/60Hz

**Our baths feature Julabo controllers, offering high precision and temperature stability solutions.**