


LAC-6

EXPLORE THE MODEL
OPTIONS AVAILABLE FOR OUR
6-LITER THERMOSTATIC BATH



LAC-6-CD:

- Precise temperature control / For internal and external applications
- Bright white displays, easily visible from a distance
- Exceptionally quiet operation
- LED temperature display
- Easy to operate / USB connection
- Class III (FL) according to DIN 12876-1
- Cabinet with electrostatic paint finish

TECHNICAL SPECIFICATIONS

- Operating temperature range: ambient +5°C to +200°C
- Temperature stability (°C): ±0.03
- Adjustment/indication resolution: 0.01°C
- Heating power (kW): 2
- Pump flow rate (l/min): 16
- Pump pressure (bar): 0.33
- Usable area (opening): 148.5 x 130 (mm) (standard and same opening as F6/F9)
- Depth: 150 (mm)
- Volume: 5.7L
- External dimensions: 18.5 x 41.3 x 44.6 cm (LxWxH)
- Total power: 2000 W
- Voltage: 230Vac 50/60Hz

LAC-6-DD:

- Precise temperature control / For internal and external applications
- Bright white displays, easily visible from a distance
- Exceptionally quiet operation
- LED temperature display
- Easy to operate / USB connection
- Class III (FL) according to DIN 12876-1
- Cabinet with electrostatic paint finish

TECHNICAL SPECIFICATIONS

- Operating temperature range: ambient +5°C to +200°C
- Temperature stability (°C): ±0.01
- Adjustment/indication resolution: 0.01°C
- Heating power (kW): 2
- Pump flow rate (l/min): 8 - 27
- Pump pressure (bar): 0.1 a 0.7bar
- Usable area (opening): 148.5 x 130 (mm) (standard and same opening as F6/F9)
- Depth: 150 (mm)
- Volume: 5.7L
- External dimensions: 18.5 x 41.3 x 44.6 cm (LxWxH)
- Total power: 2000 W
- Voltage: 230Vac 50/60Hz

LAC-F6-CD:

- Precise temperature control / For internal and external applications
- Bright white displays, easily visible from a distance
- Exceptionally quiet operation
- LED temperature display
- Easy to operate / USB connection
- Class III (FL) according to DIN 12876-1

TECHNICAL SPECIFICATIONS

- Operating temperature range: -20°C to +150°C
- Temperature stability (°C): ±0.03
- Adjustment/indication resolution: 0.01°C
- Heating power (KW): 2
- Pump flow rate (l/min): 16
- Pump pressure (bar): 0.33
- Usable area (opening): 148.5 x 130 (mm)
- Depth: 150 (mm)
- Volume: 5.7L
- External dimensions: 21 x 52.1 x 65.5 cm (LxWxH)
- Total power: 2300 W
- Voltage: 230Vac 50/60Hz

LAC-F6-DD:

- Precise temperature control / For internal and external applications
- Bright white displays, easily visible from a distance
- Exceptionally quiet operation
- LED temperature display
- Easy to operate / USB connection
- Class III (FL) according to DIN 12876-1

TECHNICAL SPECIFICATIONS

- Operating temperature range: -20°C to +150°C
- Temperature stability (°C): ±0.01
- Adjustment/indication resolution: 0.01°C
- Heating power (kW): 2
- Pump flow rate (l/min): 8 - 27
- Pump pressure (bar): 0.1 to 0.7 bar
- Usable area (opening): 148.5 x 130 (mm)
- Depth: 150 (mm)
- Volume: 5.7L
- External dimensions: 21 x 52.1 x 65.5 cm (LxWxH)
- Total power: 2300 W
- Voltage: 230Vac 50/60Hz

Our baths feature Julabo controllers, offering high precision and temperature stability solutions.