



LAC-9

EXPLORE THE MODEL
OPTIONS AVAILABLE FOR OUR
9-LITER THERMOSTATIC BATH



LAC-9-CD:

- Precise temperature control / For internal and external applications
- Bright white displays, clearly visible from a distance
- Exceptionally quiet operation
- LED temperature indication
- Simple operation / USB connection
- Class III (FL) compliant with DIN 12876-1
- Electrostatic-coated housing

TECHINICAL SPECIFICATIONS

- Working temperature range: Ambient +5°C to +200°C
- Temperature constancy: $\pm 0.03^{\circ}\text{C}$
- Adjustment/indication resolution: 0.01°C
- Heating power: 2 kW
- Pump flow rate: 16 L/min
- Pump pressure: 0.33 bar
- Usable area (opening): 130 x 145 mm
- Depth: 200 mm
- External dimensions: 29.6 x 43.6 x 44.3 cm (WxDxH)
- Volume: 9 L
- Total power: 2000
- Voltage: 230Vac 50/60Hz

LAC-9-DD:

- Precise temperature control / For internal and external applications
- Bright white displays, clearly visible from a distance
- Exceptionally quiet operation
- LED temperature indication
- Simple operation / USB connection
- Class III (FL) compliant with DIN 12876-1
- Electrostatic-coated housing

TECHINICAL SPECIFICATIONS

- Working temperature range: Ambient +5°C to +200°C
- Temperature constancy: $\pm 0.01^{\circ}\text{C}$
- Adjustment/indication resolution: 0.01°C
- Heating power: 2 kW
- Pump flow rate: 8–27 L/min
- Pump pressure: 0.1–0.7 bar
- Usable area (opening): 130 x 145 mm
- Depth: 200 mm
- Volume: 9 L
- External dimensions: 29.6 x 43.6 x 44.3 cm (WxDxH)
- Total power: 2000 W
- Voltage: 230Vac 50/60Hz

LAC-F9-CD:

- Precise temperature control / For external applications
- Bright white displays, clearly visible from a distance
- Exceptionally quiet operation
- LED temperature indication
- Simple operation / USB connection
- Class III (FL) compliant with DIN 12876-1

TECHINICAL SPECIFICATIONS

- Working temperature range: -20°C to $+150^{\circ}\text{C}$
- Temperature stability ($^{\circ}\text{C}$): ± 0.03
- Adjustment/indication resolution: 0.01°C
- Heating power (KW): 2
- Pump flow rate (l/min): 16
- Pump pressure (bar): 0.33
- Usable area (opening): 130 x 145mm
- Depth: 200mm
- Volume: 9L
- External dimensions: 21 x 52.1 x 65 cm (WxDxH)
- Total power: 2300 W
- Voltage: 230Vac 50/60Hz

LAC-F9-DD:

- Precise temperature control / For external applications
- Bright white displays, clearly visible from a distance
- Exceptionally quiet operation
- LED temperature indication
- Simple operation / USB connection
- Class III (FL) compliant with DIN 12876-1

TECHINICAL SPECIFICATIONS

- Working temperature range: -20°C to $+150^{\circ}\text{C}$
- Temperature stability ($^{\circ}\text{C}$): ± 0.01
- Adjustment/indication resolution: 0.01°C
- Heating power (kW): 2
- Pump flow rate (l/min): 8 - 27
- Pump pressure (bar): 0.1 to 0.7 bar
- Usable area (opening): 130 x 145mm
- Depth: 200mm
- Volume: 9L
- External dimensions: 21 x 52.1 x 65 cm (WxDxH)
- Total power: 2300 W
- Voltage: 230Vac 50/60Hz

Our baths feature Julabo controllers, offering high precision and temperature stability solutions.