

FOAM TESTER – FT

SPECIFICATIONS



Product specifications

Foam Tester

Line sensor

Sensor resolution	1728 × 1 px
Spatial resolution	200 dpi 0.125 mm
Temporal resolution	5 fps
Scanning length	216 mm

Operating system

Gas flow rate (internal)	0.2 to 1.0 L/min
Gas flow rate (external)	0.05 to 1.0 L/min
Approved gases	air, nitrogen, carbon dioxide
Approved pressure	5 ± 0.5 bar
Approved temperature	4 to 90 °C

Illumination

Type	LED
Wave length, dominant	469 nm (IR: 850 nm)

Software

ADVANCE	foam analysis
---------	---------------

Measurement specifications

Foam Tester

Analyzed foam characteristic

foamability and foam stability

Results

- foam height
- liquid height
- total height
- foam capacity
- foam half life time
- drainage half life time
- sample temperature

General specifications**Foam Tester****Sample dimensions**

Minimum required sample volume 50 mL with 40 mm diameter column

Temperature control

Type double-walled glass column

Range 4 to 90 °C ¹⁾

Resolution 0.1 °C

Temperature measurement

Sensor PT100

Range 4 to 90 °C

Resolution 0.1 °C

Precision 0.1 °C

Accuracy 1/3 DIN B (± 0.1 °C at 0 °C, ± 0.8 °C at 400 °C)

Location inside sample liquid

Environment

Operating temperature 15 to 30 °C

Humidity without condensation

Instrument dimensions

Footprint 245 mm × 275 mm (W × D)

Height 460 mm

Weight (without accessories) 9 kg

Power supply

Voltage 100 to 240 VAC

Power consumption maximum 30 W

Frequency 50 to 60 Hz

Interfaces

PC 1× USB 2.0

Accessories

Glass columns 40 mm diameter, temperature control option

Material of columns and filters column: borosilicate glass, norm: ISO 4793, filter paper: cellulose

Material of sealings silicone and FKM

¹⁾ additional thermostat needed: TB14

